### SUMMARY OF UNIAXIAL COMPRESSIVE STRENGTH TEST RESULTS




PO Box 30591 Edmond, OK 73003 405-562-3328

RRC PROJECT 20021

PROJECT NAME: Soil Stabilization Sample Lab Testing
CLIENT: SoilChem

Boring	Depth	Length	Diameter	L/D	Moisture	Unit Weight	Loading Rate	Un Comp Strength	Un Comp Strength	Correction Factor Applied	Straight	Flat	Perpend
	(ft)	(in)	(in)		%	(pcf)	(KN/sec)	(Mpa)	(psi)	Applied		Pass / Fai	il
1226+00	N/A	4.432	3.964	1.12	1.1%	120.0	0.01	4.0	587	N/A	Pass	Pass	Pass
1191+00	N/A	4.508	3.948	1.14	1.8%	118.6	0.03	3.6	521	N/A	Pass	Pass	Pass
1249+00	N/A	4.533	3.953	1.15	0.9%	118.7	0.04	3.1	452	N/A	Pass	Pass	Pass
1251+00	N/A	4.492	3.932	1.14	1.2%	123.9	0.04	5.5	800	N/A	Pass	Pass	Pass



Compressive Strength = **Photo After Test** 587 psi

### **Test Conditions**

Procedure S1 - Side Staightness = Pass Procedure FP2 - Flatness = Pass Procedure P2 - Perpendicularity = Pass Load Direction = Vertical

Loading Rate = 0.01 KN/sec Time of Failure = 3252.7 seconds °C Temperature at Testing =


### **Equipment Used**

Caliper - General No. 143

Feeler Gauge



SAMPI	LE DATA	PROJECT INFORMATION			
SAMPLE LOCATION:	1226+00	PROJECT:	Soil Stabilized Sample Lab Testing		
SAMPLE DESCRIPTION:	Stabilized Soil	LOCATION:	Oklahoma		
MOISTURE CONTENT:	1.1%	PROJECT NO.:	20021		
UNIT WEIGHT (PCF):	120.0	CLIENT:	SoilChem		
DIAMETER (IN):	3.964	TESTED BY:	SAH		
LENGTH (IN):	4.432	DATE:	4/17/2020		
L/D RATIO:	1.12	RED ROCK CONSULTING			



Compressive Strength =

521

psi

**Photo After Test** 

### **Test Conditions**

Procedure S1 - Side Staightness = Pass
Procedure FP2 - Flatness = Pass
Procedure P2 - Perpendicularity = Pass
Load Direction = Vertical

 $\begin{array}{ccc} \text{Loading Rate} = & 0.04 & \text{KN/sec} \\ \text{Time of Failure} = & 727.1 & \text{seconds} \\ \text{Temperature at Testing} = & 25 & ^{\circ}\text{C} \\ \end{array}$ 


### **Equipment Used**

Caliper - General No. 143

Feeler Gauge



SAMPI	LE DATA	PRO	PROJECT INFORMATION			
SAMPLE LOCATION:	1191+00	PROJECT:	Soil Stabilized Sample Lab Testing			
SAMPLE DESCRIPTION:	Stabilized Soil	LOCATION:	Oklahoma			
MOISTURE CONTENT:	1.8%	PROJECT NO.:	20021			
UNIT WEIGHT (PCF):	118.6	CLIENT:	SoilChem			
DIAMETER (IN):	3.948	TESTED BY:	SAH			
LENGTH (IN):	4.508	DATE:	4/17/2020			
L/D RATIO: 1.14			ED ROCK ONSULTING			



Compressive Strength =

452

psi

**Photo After Test** 

### **Test Conditions**

Procedure S1 - Side Staightness = Pass
Procedure FP2 - Flatness = Pass
Procedure P2 - Perpendicularity = Pass
Load Direction = Vertical

Loading Rate = 0.04 KN/sec
Time of Failure = 631.7 seconds
Temperature at Testing = 25 °C


## **Equipment Used**

Caliper - General No. 143

Feeler Gauge



SAMP	LE DATA	PR	PROJECT INFORMATION			
SAMPLE LOCATION:	1249+00	PROJECT:	Soil Stabilized Sample Lab Testing			
SAMPLE DESCRIPTION:	Stabilized Soil	LOCATION:	Oklahoma			
MOISTURE CONTENT:	0.9%	PROJECT NO.:	20021			
UNIT WEIGHT (PCF):	118.7	CLIENT:	SoilChem			
DIAMETER (IN):	3.953	TESTED BY:	SAH			
LENGTH (IN):	4.533	DATE:	4/17/2020			
L/D RATIO: 1.15			RED ROCK CONSULTING			



Compressive Strength =

800

psi

**Photo After Test** 

### **Test Conditions**

Procedure S1 - Side Staightness = Pass
Procedure FP2 - Flatness = Pass
Procedure P2 - Perpendicularity = Pass

Load Direction = Vertical

 $\begin{array}{ccc} \text{Loading Rate} = & 0.04 & \text{KN/sec} \\ \text{Time of Failure} = & 1097.2 & \text{seconds} \\ \text{Temperature at Testing} = & 25 & ^{\circ}\text{C} \\ \end{array}$ 

## **Equipment Used**

Caliper - General No. 143

Feeler Gauge



SAMP	LE DATA	PF	PROJECT INFORMATION			
SAMPLE LOCATION:	1251+00	PROJECT:	Soil Stabilized Sample Lab Testing			
SAMPLE DESCRIPTION:	Stabilized Soil	LOCATION:	Oklahoma			
MOISTURE CONTENT:	1.2%	PROJECT NO.:	20021			
UNIT WEIGHT (PCF):	123.9	CLIENT:	SoilChem			
DIAMETER (IN):	3.932	TESTED BY:	SAH			
LENGTH (IN):	4.492	DATE:	4/17/2020			
L/D RATIO: 1.14		RED ROCK CONSULTING				